



HAIKU

DEEP SOUL

MIRAGE[®]
Porcelain. Design. Sustainability

HAIKU

DEEP SOUL

THE UNEXPECTED combination

5 colori di Cottoemento dal design contemporaneo.

Una reinterpretazione ceramica delle lastre in cemento

contaminata elegantemente dal pregio antico di

terrecotte umbre, toscane e francesi,

per soluzioni in grado di sposare gusto, tradizione e innovazione.



THE UNEXPECTED combination

5 colours of Cottoemento with a contemporary design.

A new ceramic take on concrete slabs, given an elegant, prestigious edge reminiscent of traditional terracotta tiles from Umbria, Tuscany and France, for tasteful solutions that team tradition with innovation.

Une SURPRENANTE combinaison

5 couleurs de Cottoemento au design contemporain.

Une réinterprétation céramique des plaques en ciment dans laquelle on retrouve l'élégance des précieuses terres cuites à l'ancienne, typiques des régions italiennes d'Ombrie et de Toscane ainsi que de la tradition française, pour des solutions alliant raffinement, legs du passé et innovation.

DIE UNERWARTETE Kombination

Die 5 Farben von Cottoemento mit zeitgemäßem Design.

Eine Neuinterpretation aus Keramik der Zementplatten mit den eleganten Einflüssen der alten meisterhaften Terrekotta-Böden aus Umbrien, der Toskana und Frankreich, für Lösungen, die Geschmack, Tradition und Innovation zu vereinen fähig sind.

UNA INESPERADA combinación

5 colores de Cottoemento de diseño contemporáneo.

Una reinterpretación en cerámica de las placas de cemento elegantemente contaminada por la belleza antigua de las terracotas de Umbría, Toscana y Francia, para soluciones que logran combinar estilo, tradición e innovación.

出人意料的组合

备有5种颜色的Cottoemento系列的设计富有现代感。

重新演绎水泥板效果的陶瓷板材

优雅再现翁布里亚、托斯卡纳和法国的古老陶土效果

打造能够将风格、传统和创新有机结合的解决方案。

HAIKU

PEPPERY HM 03



FLOOR:
Peppery **HM 03** NAT SQ
150x600 / 6"x24"
WALL and COUNTER:
NORR Grå **RR 02** NAT SQ
1200x2780 / 48"x110"
GLOCAL Iron **GC 20** SP SQ
1600x3200 / 63"x126"



HAIKU

TAN HM 04



FLOOR:
Tan **HM 04** SAT SQ
750x750 / 30"x30"



HAIKU

PEPPERY HM 03



FLOOR:
Peppery HM 03 ST SQ
900x900 / 36"x36" x 20 mm EVO_2/E

HAIKU

PEARLY HM 01



FLOOR:
Charme Maiolica di Sant'Antonio Black
150x150 / 6"x6"
WALL:
Pearly **HM 01** NAT SQ
300x600 / 12"x24"

HAIKU

PEPPERY HM 03



FLOOR:
Peppery **HM 03** NAT SQ
300x300 / 12"x12"
WALL:
Charme Brick Scraped NAT NO SQ
75x300 / 3"x12"



HAIKU

LICORICE HM 06
PEPPERY HM 03



FLOOR:
Licorice HM 06 NAT SQ
600x600 / 24"x24"

WALL:
Licorice HM 06 NAT SQ
150x600 / 6"x24"
Peppery HM 03 NAT SQ
300x600 / 12"x24"

HAIKU

LICORICE **HM 06**
PEPPERY **HM 03**



FLOOR:
Licorice **HM 06** NAT SQ
600x600 / 24"x24"
WALL:
Licorice **HM 06** NAT SQ
150x600 / 6"x24"
Peppery **HM 03** NAT SQ
300x600 / 12"x24"



HAIKU

TAN HM 04



FLOOR:
Tan **HM 04** NAT SQ
600x600 / 24"x24"
WALL:
JURUPA Camp **JP 04** NAT SQ
200x1200 / 8"x48"

HAIKU

PEPPERY HM03



FLOOR:
Peppery **HM 03** NAT SQ
600x600 / 24"x24"
WALL:
Charme Maiolica di Sant'Antonio Black
150x150 / 6"x6"

HAIKU

PEARLY HM 01



FLOOR:
Pearly **HM 01** NAT SQ
600x600 / 24"x24"
WALL:
Charme Brick Tan **HM 04** NAT NO SQ
75x300 / 3"x12"



HAIKU
CAMEL HM 02



FLOOR:
Camel **HM 02** NAT SQ
300x600 / 12"x24"

PEARLY HM 01



9 mm

750x750 / 30"x30"
NAT SQ / SAT SQ

600x600 / 24"x24"
NAT SQ

300x600 / 12"x24"
NAT SQ

150x600 / 6"x24"
NAT SQ

300x300 / 12"x12"
NAT SQ



Stucchi consigliati
Recommended grouts

KERAKOLL	02 Grigio Luce	
MAPEI	111 Grigio Argento	
LATICRETE	88 Silver Shadow	

Shade variation



Moderate variation

CAMEL HM 02



9 mm

750x750 / 30"x30"
NAT SQ / SAT SQ

600x600 / 24"x24"
NAT SQ

300x600 / 12"x24"
NAT SQ

150x600 / 6"x24"
NAT SQ

300x300 / 12"x12"
NAT SQ



Stucchi consigliati
Recommended grouts

KERAKOLL	03 Grigio Perla	
MAPEI	110 Manhattan	
LATICRETE	89 Smoke Grey	

Shade variation



Moderate variation

PEPPERY HM 03



± 9 mm

750x750 / 30"x30"
NAT SQ / SAT SQ

600x600 / 24"x24"
NAT SQ

300x600 / 12"x24"
NAT SQ

150x600 / 6"x24"
NAT SQ

300x300 / 12"x12"
NAT SQ

± 20 mm **GO 2/e**

900x900 / 36"x36"
ST SQ



Stucchi consigliati
Recommended grouts

KERAKOLL	04 Grigio Ferro	
MAPEI	113 Grigio Cemento	
LATICRETE	34 Sand Stone	

Shade variation



Moderate variation

TAN HM 04



± 9 mm

750x750 / 30"x30"
NAT SQ / SAT SQ

600x600 / 24"x24"
NAT SQ

300x600 / 12"x24"
NAT SQ

150x600 / 6"x24"
NAT SQ

300x300 / 12"x12"
NAT SQ

± 20 mm **GO 2/e**

900x900 / 36"x36"
ST SQ



Stucchi consigliati
Recommended grouts

KERAKOLL	04 Grigio Ferro	
MAPEI	112 Grigio Medio	
LATICRETE	78 Sterling Silver	

Shade variation



Moderate variation

LICORICE HM 06



9 mm

600x600 / 24"x24"
NAT SQ

300x600 / 12"x24"
NAT SQ

150x600 / 6"x24"
NAT SQ

300x300 / 12"x12"
NAT SQ

20 mm
GO 2/e

900x900 / 36"x36"
ST SQ



Stucchi consigliati
Recommended grouts

KERAKOLL	05 Antracite	
MAPEI	114 Antracite	
LATICRETE	45 Raven	

Shade variation



Moderate variation

HAIKU

LICORICE HM 06



FLOOR:
Licorice **HM 06** NAT SQ
600x600 / 24"x24"

RIASSUNTIVO FORMATI E IMBALLI

SUMMARY OF SIZES AND PACKAGING













ÜBERSICHT ÜBER FORMATE UND VERPACKUNGEN






RÉCAPITULATIF FORMATS ET EMBALLAGES

SINÓPTICO DE FORMATOS Y EMBALAJES

КРАТКАЯ ИНФОРМАЦИЯ О ФОРМАТАХ И УПАКОВКАХ

规格和包装概述

													
	750x750 30"x30"	600x600 24"x24"	300x600 12"x24"	150x600 6"x24"	300x300 12"x12"	900x900 36"x36"	Mosaico 36T* 300x300 12"x12"	Battiscopa** 72x600 27/8"x24"	Gradino A** 300x600 12"x24"	Gradino G** 300x600 12"x24"	Gradino B 330x600 13 1/8"x24"	Gradino B Ang. 330x330 13 1/8"x13 1/8"	
	FORMATI - SIZES							PEZZI SPECIALI - SPECIAL PIECES					
Spessore - Thickness	± 9 mm						± 20 mm	DECORI - DECORS					
Superficie - Surface	NAT	SAT	NAT SQ	NAT SQ	NAT SQ	NAT SQ	ST SQ	NAT	NAT	NAT	NAT	NAT	
PEARLY HM 01	UK37	UH24	SQ26	SQ21	SU21	UJ18	-	SR43	SS08	TB29	TB34	TB44	TB39
CAMEL HM 02	UK38	UH25	SQ27	SQ22	SU22	UJ19	-	SR44	SS09	TB30	TB35	TB45	TB40
PEPPERY HM 03	UK39	UH26	SQ28	SQ23	SU23	UJ20	UH30	SR45	SS10	TB31	TB36	TB46	TB41
TAN HM 04	UK40	UH27	SQ29	SQ24	SU24	UJ21	UH31	SR46	SS11	TB32	TB37	TB47	TB42
LICORICE HM 06	-	-	SQ30	SQ25	SU25	UJ22	UH32	SR47	SS12	TB33	TB38	TB48	TB43

 Peso lordo per scatola Gross weight per box Bruttogewicht pro Karton Poids brut par boîte Peso bruto por caja Вес брутто коробки	23,26	23,58	26,10	26,92	22,50	37,60	12,40	10	7	7	4	4
 Pezzi per scatola Pieces for box Stück pro Karton Pièces pour boîte Piezas por caja Штук в коробке	2	3	7	14	12	1	6	-	-	-	-	-
 mq. scatola mq. box mq. Karton mq. boîte mq. caja кв.м в коробке	1,125	1,08	1,26	1,26	1,08	0,81	0,54	-	-	-	-	-
 Scatole / full pallet Boxes / full pallet Stück / volle Palette Pièces / palette complete Cajas / pallet completo Коробок в палете	42	40	40	40	48	18	60	-	-	-	-	-
 mq./pallet	47,25	43,20	50,40	50,40	51,84	14,58	32,4	-	-	-	-	-

Materiale rettificato e monocalibro - Squared and monocaliber - Ware nachkalibriert und im monokaliber - Materiel rectifié et a un sol calibre
Material rectificado y monocalibre - Ректифицированный и однокалиберный материал во всех форматах и с любым типом поверхности

A: Disponibile - Available - Available - Lieferbar - Disponible - Disponible - Доступный

* **Decoro su rete** - Mesh-backed decoration - Dekor auf Netz - Décor sur filet - Decoración en red - Декор в сети

** **Finitura a becco di civetta** - One-round edge shaping - Ausführung mit Eckabrundung - Façonnage à bord rond - Acabado canto romo - Плитка с завалом

NAT: Naturale - Natural | **ST: Strutturata 20 mm** - Structured 20 mm | **SAT: Satinato**



STANDARD EN 14411 - G

	CARATTERISTICHE TECNICHE TECHNICAL DATA TECHNISCHE DATEN CARACTERISTIQUES TECHNIQUES CARACTERISTICAS TÉCNICAS ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ 技术特征	NORMA STANDARD NORM NORME NORMA НОРМА ЗНАЧЕНИЯ 标准	VALORI PRESCRITTI DALLE NORME EN 14411 - G INTERNATIONAL STANDARDS EN 14411 - G INTERNATIONALE NORMWERTE EN 14411 - G VALEURS PREVUES PAR LES NORMES EN 14411 - G VALORES PREVISTOS POR LAS NORMAS EN 14411 - G ПРЕДУСМОТРЕННЫЕ СТАНДАРТОМ EN 14411-G EN 14411 - G标准规定值	*VALORE MEDIO MIRAGE MIRAGE AVERAGE VALUE MIRAGE MITTELWERT VALEURS MOYEN MIRAGE VALOR MEDIO MIRAGE СРЕДНЕЕ ЗНАЧЕНИЕ MIRAGE MIRAGE平均值		
	CARATTERISTICHE DIMENSIONALI - SIZE CHARACTERISTICS - MASSEIGENSCHAFTEN DETERMINATION DES CARACTERISTIQUES DIMENSIONELLES - CARACTERISTICAS DIMENSIONALES - РАЗМЕРНЫЕ ХАРАКТЕРИСТИКИ - 尺寸特征					
	LATI SIDES - SEITEN COTES - CANTOS РАЗМЕРЫ СТОРОН - 側边	EN ISO 10545-2	± 0,6% MAX (± 2,0 mm MAX)	CONFORME COMPLYING		
	SPESSORE THICKNESS - DICKE ÉPAISSEUR - ESPESOR ТОЛЩИНА - 厚度	EN ISO 10545-2	± 5,0% MAX (± 0,5 mm MAX)	CONFORME COMPLYING		
	RETTILINEITÀ DEGLI SPIGOLI STRAIGHTNESS OF SIDES - GERADLINIGKEIT DER KANTEN RECTITUDE DES ARÊTES - RECTITUD DE LOS CANTOS КОСОУГОЛЬНОСТЬ - 边角平直度	EN ISO 10545-2	± 0,5% MAX (± 1,5 mm MAX)	CONFORME COMPLYING		
	ORTOGONALITÀ RECTANGULARITY - RECHTWINKLIGKEIT PERPENDICULARITÉ - ORTOGONALIDAD КРИВИЗНА СТОРОН - 直角度	EN ISO 10545-2	± 0,5% MAX (± 2,0 mm MAX)	CONFORME COMPLYING		
	PLANARITÀ SURFACE FLATNESS - EBENFLÄCHIGKEIT PLANEITE DE SURFACE - PLANEIDAD КРИВИЗНА ЛИЦЕВОЙ ПОВЕРХНОСТИ - 平整度	EN ISO 10545-2	± 0,5% MAX (± 2,0 mm MAX)	CONFORME COMPLYING		
	ASSORBIMENTO D'ACQUA WATER ABSORPTION - WASSERAUFNAHME ABSORPTION D'EAU - ABSORCIÓN DE AGUA ВОДОПОГЛОЩЕНИЕ - 吸水率	EN ISO 10545-3	≤ 0,5%	≤ 0,1%		
	RESISTENZA ALLA FLESSIONE FLEXION RESISTANCE - BIEGEFESTIGKEIT RESISTANCE A LA FLEXION - RESISTENCIA A LA FLEXIÓN ПРЕДЕЛ ПРОЧНОСТИ ПРИ ИЗГИБЕ - 抗弯强度	EN ISO 10545-4	S ≥ 700 N (< 7,5 mm) S ≥ 1.300 N (> 7,5 mm) R ≥ 35 N/mm².	≠ 9 mm: S≥2.400N R≥48 N/mm² ≠ 20 mm: S≥12.500N R≥48 N/mm²		
	RESISTENZA ALL'URTO IMPACT RESISTANCE - STOSSEFESTIGKEIT RESISTANCE AUX CHOCES - RESISTENCIA A LOS GOLPES УДАРОСТОЙКОСТЬ - 抗冲击强度	EN ISO 10545-5	VALORE DICHIARATO DECLARED VALUE	> 0,80		
	RESISTENZA ALL'ABRAZIONE ABRASION RESISTANCE - ABRIEBFESTIGKEIT RESISTANCE A L'ABRASION - RESISTENCIA A LA ABRASIÓN СТОЙКОСТЬ К ИСТИРАНИЮ - 耐磨强度	EN ISO 10545-6	≤ 175 mm³	< 150 mm³		
	COEFFICIENTE DI DILATAZIONE TERMICA LINEARE COEFFICIENT OF LINEAR THERMAL-EXPANSION - LINEARER WÄRMEAUSSDEHNUNGSKOEFFIZIENT COEFFICIENT DE DILATATION THERMIQUE LINEAIRE - COEFICIENTE DE DILATACIÓN TÉRMICA LINEAL КОЭФФИЦИЕНТ ЛИНЕЙНОГО ТЕРМИЧЕСКОГО РАСШИРЕНИЯ - 线性热膨胀系数	EN ISO 10545-8	—	α=7,3x10 ⁻⁶ °C ⁻¹		
	RESISTENZA AGLI SBALZI TERMICI RESISTANCE TO THERMAL SHOCKS - BESTÄNDIGKEIT GEGEN TEMPERATURSCHWANKUNGEN RESISTANCE AUX CHOCES THERMIQUES - RESISTENCIA A LOS CHOQUES TERMICOS СТОЙКОСТЬ К ПЕРЕПАДАМ ТЕМПЕРАТУРЫ - 耐热突变性	EN ISO 10545-9	TEST SUPERATO SECONDO EN ISO 10545-1 PASS ACCORDING EN ISO 10545-1	NESSUN DANNO NO DAMAGE		
	RESISTENZA AL GELO FROST RESISTANCE - FROSTBESTÄNDIGKEIT RESISTANCE AU GEL - RESISTENCIA AL HIELO МОРОЗОСТОЙКОСТЬ - 耐冻性	EN ISO 10545-12	TEST SUPERATO SECONDO EN ISO 10545-1 PASS ACCORDING EN ISO 10545-1	NESSUN DANNO NO DAMAGE		
	RESISTENZA ALL'ATTACCO CHIMICO RESISTANCE TO CHEMICALS - CHEMIKALIENBESTÄNDIGKEIT RESISTANCE A L'ATTAQUE CHIMIQUE - RESISTENCIA QUÍMICA ХИМИЧЕСКАЯ СТОЙКОСТЬ - 耐化学品作用	EN ISO 10545-13	B MIN.	A LA HA		
	RESISTENZA ALLE MACCHIE RESISTANCE TO STAINS - FLECKENBESTÄNDIGKEIT RESISTANCE AUX TACHES - RESISTENCIA A LAS MANCHAS УСТОЙЧИВОСТЬ К ПЯТНООБРАЗОВАНИЮ - 防污性	EN ISO 10545-14	VALORE DICHIARATO DECLARED VALUE	5		
	CESSIONE DI PIOMBO E CADMIO LEAD AND CADMIUM DISCHARGE - ABGABE VON BLEI UND CADMIUM PERTE DE PLOMB ET CADMIUM - CESIÓN DE PLOMO Y CADMIO ВЫДЕЛЕНИЕ СВИНЦА И КАДМИЯ - 铅和镉的排放	EN ISO 10545-15	VALORE DICHIARATO DECLARED VALUE	< AL LIMITE DI RILEVAMENTO < THAN INSTRUMENT LIMIT		
				NAT	SAT	ST 20mm
		DM. 236/89 BCRA	> 0,40	> 0,40	-	> 1
		ASTM C1028	Dry SCOF > 0,60	> 0,60	-	> 0,85
		ANSI A137.1	Wet DCOF > 0,42	> 0,42	-	> 0,65
		DIN 51130	-	R9	-	R11
		DIN 51097	-	-	-	A+B+C
		ENV 12633	≥ CL1	CL1	-	CL2
		BS 7976	≥ 36	> 36	-	> 36
		TecnoTest - G3357-02	-	GS4 GB3	-	-
	SCIVOLOSITÀ SKID RESISTANCE - RUTSCHWERT GLISSANCE - ADHERENCIA СКОЛЬЗКОСТЬ - 防滑性					

Per i certificati specifici, contattare Mirage SpA - For specific certificates, please contact Mirage SpA - Für die speziellen Zertifikate wenden Sie sich bitte an Mirage SpA - Pour les certificats spécifiques, veuillez contacter Mirage SpA
Para los certificados específicos, contactar Mirage SpA - Для сертификатов обращайтесь в компанию Mirage SpA - 关于具体的证书, 请联系Mirage SpA公司

www.mirage.it



Made in Italy

www.mirage.it



Mirage Granito Ceramico S.p.a.

41026 - Pavullo (MO) ITALY - Via Giardini Nord, 225
Tel. +39 0536 29611 - Fax +39 0536 21065
info@mirage.it - www.mirage.it

Mirage Project Point

20121 - Milano ITALY
Via Marsala, 7
Tel. +39 02 65560879

projectpoint-mi@mirage.it
www.mirageprojectpoint.com/milano

Mirage USA INC.

618 Grassmere Park Dr - Suite 1-2
Nashville - Tennessee (TN) - 37211
Ph. +1 615 834 3888
TAX ID: 75 2773306

info@mirageusa.net
www.mirageusa.net

Mirage Project Point Dubai

Building 7 - Ground Floor
d3 Dubai Design District
United Arab Emirates
Ph. +971 4 554 3944
Licence No. 93659

projectpoint-uae@mirage.it
www.mirageprojectpoint.com/dubai